

Hurricane Cable Blowing Machine

The C-1750 Hurricane has been designed to maximise protection for micro cables with a compliant double drive concept, backed by the latest technology in servo controls to provide precise control of torque and speed. Single person operation with safe, easy to operate ergonomic controls combines with low maintenance and high reliability to form the machine's key features. The C-1750 is adjustable to suit a wide range of cable diameters 2.5-14mm.

Main Features

- Automatic Cable centralising.
- Synchronous high grip profiled compliant drive belts.
- Vertical design with ergonomic controls for ease of operation.
- Forward and reverse.
- Variable torque and speed controls via remote.
- Digital servo motor drive system.
- Auto stop facility when air stone fitted.
- Single person operation.
- Digital cable speed and length monitoring.
- Integral air valve and pressure gauge.
- Optional automated pressure control system.
- Easy cable threading.
- Polycarbonate safety guarding.
- Lightweight and compact.
- Low maintenance.
- Low noise levels.
- Travel case.
- Tool kit.
- Advanced data logging measuring speed, force, distance, GPS location and environmental conditions

000000



Product No

Description

C-1750

Hurricane Cable Blowing Machine

Specification

Cable Diameter:2.5 to 14mmTube Size (Outside Dia):5 to 25mmCable Speed (Adjustable):0-85m/minPushing Force:400NAir Pressure:15 Bar MaxPower Requirement:220/110 VAC


E-mail: sales@cbsproducts.com • Website: www.cbsproducts.com



Hurricane Configuration for Cable Blowing

In order to customise your Hurricane to your application, please select one each from the list below, the Tube Collet Assembly (A), the Cable Guide Assembly (B) and the Cable Seals (C).

When ordering, please have Tube and Cable dimensions available.



A) Tube Collet & Clamp Assemblies

Product No	Description
C-1750-TBC-5 C-1750-TBC-7 C-1750-TBC-8 C-1750-TBC-10 C-1750-TBC-12 C-1750-TBC-14 C-1750-TBC-16 C-1750-TBC-18 C-1750-TBC-20	Tube Collet Assy – 05mm o/d Tube Collet Assy – 07mm o/d Tube Collet Assy – 08mm o/d Tube Collet Assy – 10mm o/d Tube Collet Assy – 12mm o/d Tube Collet Assy – 14mm o/d Tube Collet Assy – 16mm o/d Tube Collet Assy – 18mm o/d Tube Collet Assy – 20mm o/d
C-1750-TBC-22 C-1750-TBC-25	Tube Collet Assy – 22mm o/d Tube Collet Assy – 25mm o/d



B) Cable Guide Assemblies

C-1750-CG-4-6 Cable Guide, 4 - 6mm Dia C-1750-CG-6-9 Cable Guide, 6 - 9mm Dia C-1750-CG-9-12 Cable Guide, 9 - 12mm Dia	Product No	Description
	C-1750-CG-4-6 C-1750-CG-6-9	Cable Guide, 6 - 9mm Dia
		Cable Guide, 12 - 14mm Dia



C) Cable Seals (pack of 5)

Description
Cable Seals 2.5 - 3.mm
Cable Seals 3 - 4mm
Cable Seals 4 - 5mm
Cable Seals 5 - 6mm
Cable Seals 6 - 7.5mm
Cable Seals 7.5 - 9mm
Cable Seals 9 - 10.5mm
Cable Seals 10.5 - 12mm
Cable Seals 12 - 14mm


For Further Information



Hurricane Spares & Accessories

Tube Seals

Tube Seals are supplied in packs of 5.



Tube Seals

Product No	Description
C-1750-TS-5	Tube Seals 5mm Dia
C-1750-TS-7	Tube Seals 7mm Dia
C-1750-TS-8	Tube Seals 8mm Dia
C-1750-TS-10	Tube Seals 10mm Dia
C-1750-TS-12	Tube Seals 12mm Dia
C-1750-TS-14	Tube Seals 14mm Dia
C-1750-TS-16	Tube Seals 16mm Dia
C-1750-TS-18	Tube Seals 18mm Dia
C-1750-TS-20	Tube Seals 20mm Dia
C-1750-TS-22	Tube Seals 22mm Dia

Replacement Drive Belts

Drive belts are supplied in pairs.



Drive Belts

Product No	Description
C-1750-DB-2.5-9	Drive Belt, 2.5 - 9mm Cable Dia
C-1750-DB-3-11	Drive Belt, 3-11mm Cable Dia
C-1750-DB-5-14	Drive Belt, 5-14mm Cable Dia