





These PATENTED slit and ring tools are designed to open fiber jackets and loose buffer tubes to provide easy fiber access. One side of the tool slits fiber jackets and loose buffer tubes, the opposite side rings fiber jackets and loose buffer tubes. All this is done without damage to the fiber. Blades are replaceable. Note: MS-326 is designed for cables used in ducts and microducts.

Simple to use:

- Select the correct groove. Grooves marked with the recommended cable size
- Place the cable in the groove to be used
- Note: The arrow on the top of the tool indicates the pulling direction and the line indicates the blade location
- Close the tool making sure lock is engaged and pull to slit the cable
- For ring operation use ring side of tool and repeat steps above, instead of pulling rotate the tool 3-6 times to ring the cable

SPECIFICATIONS	MS-306	MS-316	MS-326	MS-426
DESCRIPTION	Mid Span Slit & Ring Tool (1.2mm-3.3mm)	Mid Span Slit & Ring Tool (2.9mm-6.8mm)	Mid Span Slit & Ring Tool (5mm-10mm)	Mid Span Slit & Ring Tool (5.8mm-12mm)
NO. OF PRECISION GROOVES	12 (6 Slitting, 6 Ringing)	10 (5 Slitting, 5 Ringing)	10 (5 Slitting, 5 Ringing)	8 (4 Slitting, 4 Ringing)
GROOVE SIZES (MM)	1.2-1.5, 1.5-1.8, 1.8-2.1, 2.1-2.5, 2.5-2.9, 2.9-3.3	2.9-3.6, 3.6-4.4, 4.4-5.2, 5.2-6.0, 6.0-6.8	5.0-5.6, 6.0-6.6, 7.2-7.8, 7.8-8.4, 9.4-10	5.8-6.4, 7.8-8.4, 9.8-10.4, 11.2-12
REPLACEMENT CARTRIDGE	MS-306RB	MS-316RB	MSB-5010	MS-426RB



Replacement Cartridges

JONARD P/N	DESCRIPTION	
MS-306RB	Replacement Blades for MS-306	
MS-316RB	Replacement Blades for MS-316	
MSB-5010	Replacement Blades for MS-326	
MS-426RB	Replacement Blades for MS-426	

MADE FOR LIFE®