

FO 103-S

Fiber Optic Stripper Line

- For stripping 250 micron buffer coating from 125 micron optical fiber
- Precision diameter hole & V-opening in blade allow for accurate buffer coating removal
- Pivot pin, spring and precision handles enhance tool functionality and durability
- Factory set, requires no adjustment
- Prevents scratching or nicking of optical fiber
- All cutting surfaces are precision formed, hardened, tempered and ground assuring precise buffer removal
- Made in the U.S.A.
- Length: 5.375 in (136.53 mm)
- Weight: 2.5 oz (71 g)



FO 103-S – Custom Applications

- The same quality FO 103-S construction is available in a variety of stripping fiber diameters
- Some models in the table below may be subject to a minimum order
- Contact Customer Service for any applications listed in the table below
U.S.: 860-635-2200 U.K.: +44-1384-400070

| Part No. | Model | Finished Cladding Diameter | |
|----------|----------------|----------------------------|---------------|
| | | (Microns) | (Inches) |
| 80355 | FO 103-S | 125 µm | .005 in. |
| 80355-1 | FO 103-S-100 | 80-100 µm | .003-.004 in. |
| 80355-15 | FO103-S-140 | 140 µm | .0055 in. |
| 80355-2 | FO 103-S-150 | 150 µm | .006 in. |
| 80355-3 | FO 103-S-162 | 162 µm | .0065 in. |
| 80355-4 | FO 103-S-007 | 175 µm | .007 in. |
| 80355-5 | FO 103-S-187.5 | 187.5 µm | .0075 in. |
| 80355-10 | FO 103-S-200 | 200 µm | .008 in. |
| 80355-12 | FO 103-S-225 | 225 µm | .009 in. |
| 80355-6 | FO 103-S-250 | 250 µm | .010 in. |
| 80355-7 | FO 103-S-280 | 275-280 µm | .011 in. |
| 80355-8 | FO 103-S-300 | 300 µm | .012 in. |
| 80355-16 | FO-103-S-400 | 400 µm | .016 in. |
| 80355-9 | FO 103-S-525 | 525 µm | .021 in. |
| 80355-17 | FO-103-S-880 | 880 µm | .035 in. |
| 80355-18 | FO-103-S-1140 | 1140 µm | .045 in. |