



## Microfocus Mid Span Slit & Ring Tool (1,2-3,3 mm) and (2,9-6,8 mm)

### Instructions

- > Select the correct groove. Grooves marked with the recommended cable size
- > Place the cable in the groove to be used
  - Note:** The arrow on the top of the tool indicates the pulling direction and the line indicates the blade location
- > To slit the cable, close the tool making sure lock is engaged and pull
- > For ring operation use ring side of tool and repeat steps above, instead of pulling rotate the tool 3-6 times to ring the cable

These **PATENTED** slit and ring tools are designed to open fiber jackets and loose buffer tubes to provide easy fiber access. One side of the tool slits fiber jackets and loose buffer tubes, the opposite side rings fiber jackets and loose buffer tubes. All this is done without damage to the fiber. Blades are replaceable.

### Specifications

	ITL103034	ITL103033
Description	Mid Span Slit & Ring Tool (1,2-3,3 mm)	Mid Span Slit & Ring Tool (2,9-6,8 mm)
No. of precision grooves	12 (6 Slitting, 6 Ringing)	10 (5 Slitting, 5 Ringing)
Groove sizes (mm)	1,2-1,5 mm   1,5-1,8 mm   1,8-2,1 mm   2,1-2,5 mm   2,5-2,9 mm   2,9-3,3 mm	2,9-3,6 mm   3,6-4,4 mm   4,4-5,2 mm   5,2-6,0 mm   6,0-6,8 mm
Cable diameters	1,2-3,3 mm	2,9-6,8 mm
Cable type	Outer Jackets, Loose Buffer Tubes	Outer Jackets, Loose Buffer Tubes