



LSA-PLUS® Series 2 Disconnection Module, 10-pair, PROFIL mounting

- Based on genuine LSA-PLUS® connection technology for use in all xDSL and ADSL2+ circuits
- Offer disconnection points for opening the line, testing in both directions or insertion of graded protection elements
- Robust long-term environmental stability allows both indoor and outdoor installation
- Compatible with accessories such as overvoltage protection magazines, labels, test and -connection cords

Product Classification

Brand	LSA-PLUS®
Product Series	LSA-PLUS Series 2
Product Type	Disconnection module
Regional Availability	EMEA

Dimensions

Width	124.00 mm 4.88 in
--------------	---------------------

Electrical Specifications

Contact Resistance, maximum	1 mOhm
Current Rating, maximum	2.00 A
Dielectric Strength	3 kV
Insulation Resistance, minimum	50000 MOhm

Environmental Specifications

Environmental Space	Indoor Outdoor
Flammability Rating	UL 94 V-0
Operating Temperature	-5 °C to +60 °C (+23 °F to +140 °F)
Relative Humidity	Up to 95%, non-condensing
Storage Temperature	-40 °C to +85 °C (-40 °F to +185 °F)

General Specifications

Color	Beige
Mount Type	PROFIL rods
Pairs, quantity	10
Package Quantity	10
Packaging Type	Box Carton

Mechanical Specifications

Conductor Gauge, solid	26-20 AWG
Conductor Gauge, stranded	26-22 AWG
Contact Base Material	Brass
Contact Plating Material	Silver
Material Type	Polybutylene terephthalate (PBT)
Plug Insertion Life, minimum	250 times
Termination Punchdowns, minimum	200 times
Termination Tool	LSA-PLUS Punchdown tool
Termination Type	IDC

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

Classification

Compliant

