

3MTM BPEO S2 EVOLUTION With 28 TRAY ORGANISER



Waterproof splice protection BPEO Evolution Size 2 BPEO Evolution is the new generation of fibre cable splice protection closures for transport, distribution and FTTH applications.

Datasheet

The product range is designed to the high standard of original BPEO closures, with the ECAM mechanical cable entry sealing and with a new generation of organisers and trays called "BPEO Evolution"

Evolution organisers and trays were developed to permit single circuit management and to allow integration of PLC splitters and other passive components into the closure.

BPEO closure size 2

Туре	: Cable Distribution Point (CDP)
	End Distribution Point (EDP),
	Branch Distribution Point (BDP)
Density	: 336 fusion splices
Or	168 mechanical splices
Or	14 splitters 1X8

Composition

The closures are delivered with an organiser with 28 slots for splice trays. The splice trays, cable entry sealings and closure fixing sup-

Features

- Unique latching mechanism for closure sealing and re-entry
- Mechanical cable entries are ECAM type
- Organiser with 3 management zones
- Storage of tubes, modules or fibres in the bottom part of the organiser
- Organiser with 28 slots for pivoting trays
- Fibre guides at the side of the organiser
- All entry ports are supplied with dummy plugs
- Pressure relief valve for flash test

Benefits

Simplified opening and closing

ports must be ordered separately.

- No flame or resin in cable entry preparation
- ECAM installation is external to the closure
- Structured storage and protection of fibre
- Trays to store 250 µm fibres
- Possible to mix tray types on the same organiser
- Excellent fibre accessibility
- Closure sealing is assured

Specification

General product features	Specifications
Cable Entry Configurations	80 milibar continuous Sealing
- CDP Cable Distribution Point	500 milibar flash test (IP68)
	Impact test Resistant to 20 Joules (IK 10)
- EDP End Distribution Point	
- BDP Branch Distribution Point	
-Double cable seal for ECAM slot D5-27 or 2 single S5-18 -Single cable seal ECAM S5-18	Pull Force Test at 1000 N on cable
-Double cable seal for ECAM slot D5-20 or 2 single S4-12 -Single cable seal ECAM S4-12	
	Dimensions with or without fixing supports (in mm)
	Support Length Width Depth
	Without 520 341 149 Wall 154 Wall/Pole 178
	Sewer 149
	Colour Black
	Material Thermoplastic

Ref. No.

<u> </u>			
	All the closures kits, size 1, 2 and 3, have the same composition:		
Closures			
	 Body and cover with valve for sealing test Fitted tray organiser 		
	 Fitted tray organiser Storage area for microstructures 		
	- All entry ports supplied plugged		
	 Instructions and installation templates included 		
	 Fixing supports and trays must be ordered separately 		
	Cable Distribution Point BPEO S2-EVOL CDP 28 Slot		
لمقهمهم	Size 2, 28 slot organiser	N501491A	501491
000 00 <u>0</u>	Secondary Distribution Point BPEO S2-EVOL CDP 28 Slot	N501492A	501492
Lyopaage	Size 2, 28 slot organiser		
LOQU UQQ	Distribution Point BPEO S2-EVOL BDP 28 Slot	N501493A	501493
	Size 2 , 28 slot organiser		
	The splice trays are selected according to		
Trays	 the type of splice (fusion or mechanical) 		
irays	 the requirement for mounting splitters 		
	- the fibre splicing capacity		
	5mm thick tray requires 1 organiser slot 10mm thick tray requires 2 organiser slots		
	10mm thick tray requires 2 organiser slots		
(T			
	BPEO-K7-1SLOT-12 fusion		E 4 4 9 6
	Compatible with fusion splice protectors 45 or 60 mm long	N541106A	541106
112	Splice tray is supplied with a cover		
and the second s			
A THERE		N541104A	541104
(Then I	BPEO-K7-2SLOT-12 fusion and PLC splitter Compatible with fusion splice protectors 45 or 60 mm long		
and a for	Can accommodate 70x10x6 mm PLC splitter		
and the second s	Splice tray is supplied with a cover		
-			
and the second s			
E 1320 4	BPEO-K7-1SLOT-6 Fibrlok 4x4	N541103A	541103
al - Jo	Compatible with mechanical splices Fibrlok 4x4 ref. 2540G Splice tray is supplied with a cover	N341103A	241102
and the second s	Spince day is supplied with a cover		
(Common of the second s			
- ET	BPEO-K7-2SLOT-12 Fibrlok 4x4		
Contractor -	Compatible with mechanical splices Fibrlok 4x4 ref. 2540G	N541108A	541108
C. E.L.P	Splice tray is supplied with a cover		
and the second			
1 and	BPEO-K7-2SLOT-10 Fibrlok with Splitter		_
the second	Can accommodate 70x10x6 mm PLC splitter	N541110A	541110
C. C. N	Splice holder for 10 Fibrlok 4x4 ref. 2540G		
and a state	Splice tray is supplied with a cover		

Cable Entry Kit

Mechanical cable entry sealing kits for single ports or double ports (for uncut cable)

The kits are supplied complete with fixing wrench. The holder and anchors are supplied in the closure.

	Double cable entry for uncut cables ECAM PAS D5-20	N721077A	721077
	Double entry cable sealing for cables from 5-20 mm diameter		
	ECAM PAS D5-27 Double entry cable sealing for cables from 5-27 mm diameter	N721069A	721069
200	Single cable entry sealing for straight-through splices or cable distribution		
	ECAM S4-12 Single entry cable sealing for cables from 4-12 mm diameter	N721079A	721079
		N721059A	721059
	ECAM S5-18 Single entry cable sealing for cables from 5-18 mm diameter		

Fixing Supports

62 62 52	Wall support for BPEO size 2 & 3	N71541A	711541
12	Pole/Wall support for BPEO size 2 & 3	N711440A	711440
	Sewer Support for BPEO size 2 & 3	N711546A	711546
R			

3M is a trademark of 3M.

Important Notice

Buyer and/or user of this 3M product has to make sure before using this product that it is suitable for the intended use. All questions of liability relating to this product are subject – in accordance with the prevailing law – to the Terms of Sale of the selling 3M subsidiary.



3M Telecommunications

Europe, Middle East & North Africa 3M Deutschland GmbH Carl-Schurz-Strasse 1 . 41453 Neuss . Germany Tel: ++49 (0)2131 / 14-5999 Fax: ++49 (0)2131 / 14-5998 Internet: www.3MTelecommunications.com

3M is trademark of the 3M company. SID is a trademark of the Quante AG.

Dr.Nr. 07-401-00500/07.2007 KL Index 0 Rights reserved to make technical alterations.