

3M™ Single ECAM EVOL S4-12 mm for BPEO




Single ECAM EVOL S4-12 mm for BPEO

The ECAM cables entries for the BPEO closures have evolved to their EVOL generation.

The new system is designed for fast & practical installation with minimum specific tooling (only Torx™ screwdriver is required)

The ECAM concept, unique in the market, allows for the preparation of the cable entry on to the cable away from the closure. Once complete the completed cable entry can be quickly plugged in to the front side of the closure

Content of the Kit



- A- 1 self adhesive cable gauge
- B- Strength Member Clamp Plate + Screw
- C- 1 gland body
- D- 1 locking fork
- E- 2 grommets
- F- 1 gland end cap
- G- 2 pairs of clamps - numbered
- H- 2 self tapping screw for clamps
- 1 installation instructions

Features

- ECAM design
- ECAM Concept
- Limited number of parts
- Components for diameter from 4 to 12 mm

Benefits

- Can be used in all the D12 ports of the BPEO closures
- Cable Preparation away from the Closure – Plug on front side – Secure with locking fork
- Easy to assemble – Minimum training
- Cover cables range for transport & distribution networks

Specification

Single Ecam EVOL S4-12

Cable Diameter from 4 to 12 mm



Water tightness = IP68

Strain Relief = 100 Kgs for central , lateral and soft strength members

Ordering Information

Ref. No.



BPEO ECAM Kit D12 Evolution
Single packaging

N530128A



BPEO ECAM Kit D12 Evolution
Bulk Packaging by 40 pcs

N721126A

BPEO Front Sides with S4-12 ports

Ref. No.



BPEO Size 1

D12 Port for Single Ecam S4-12



CDP & EDP front side



501488



BPEO Size 2




501489



BPEO Size 3

EDP & BDP Front side



501492

501493



501495

501496

Important Notice

The details contained in this literature have been carefully prepared from information available to 3M at the time of its production. However, it is not intended to be relied upon for purposes of product specification and you should contact your sales representative if specification details are required. Because of the wide variety of processes and conditions in which these products may be used, the user should first carry out tests to determine the suitability of the products for the particular use intended. All questions of warranty and liability relating to 3M products are governed by the selling 3M subsidiary's Terms of Sale subject where applicable to the prevailing law.

3M is trademark of the 3M company.



3M Communication Markets Division
3M United Kingdom Plc
 3M Centre
 Cain Road
 Bracknell
 Berkshire RG12 8HT
 Internet: www.3M.com

Rights reserved to make technical alternations
 Dr.Nr.07-401-392 Index 0 - UK

3M Communication Markets Division
3M Ireland Limited
 Iveagh Building,
 The Park,
 Carrickmines,
 Dublin 18 | Ireland