

P-CABLE

# P-CABLE Basic HRK data sheet

## P-CABLE Basic HRK with super segment ring technology

### A new generation of press seals.

The P-CABLE Basic HRK featuring super segment ring technology is a press seal that offers outstanding value for money, ease of installation and versatility. The inscribed segment rings make it extremely simple to adapt the press seal to the cable configuration and retrofit it on site. Just six variants are enough to cover the majority of standard applications for 100 and 150 mm drill holes/wall sleeves. Thanks to its flexibility and low price, the P-CABLE Basic HRK is perfect for keeping in stock.



P-CABLE Basic SSG  
Example: HRK 100-SSG-4/8-30

### P-CABLE Basic SSG – the advantages at a glance.

- Inscribed segment rings
- Split seal, making it retrofittable
- For standard applications in 100 or 150 mm drill holes/wall sleeves
- Blind plugs for unoccupied ducts are included in scope of delivery
- Sealing width of 40 mm
- EPDM sealing material
- Highly robust plastic pressure plates made of polyamide 6.6 with 30% glass fibre
- Absolutely gas- and watertight
- Suitable for water-impermeable concrete, stress class 1



Split design,  
inscribed application range

# Technical data for P-CABLE Basic HRK

| Core drilling/<br>wall sleeve<br>Ø <sub>i</sub> (mm) | Number<br>cable configuration | Application range<br>cable Ø (mm) | Article code         |
|--|-------------------------------|-----------------------------------|----------------------|
| 100  | 1                             | 18 - 65                           | HRK 100-SSG-1/18-65* |
|  | 4                             | 8 - 30                            | HRK 100-SSG-4/8-30*  |
| 150  | 1                             | 36 - 70                           | HRK 150-SSG-1/36-70  |
|  | 1                             | 70 - 112                          | HRK 150-SSG-1/70-112 |
|  | 3                             | 24 - 54                           | HRK 150-SSG-3/24-54* |
|  | 6                             | 10 - 36                           | HRK 150-SSG-6/10-36* |

\*incl. blind plug

## Tools & accessories

### Assembly kit HSI 150-DG

consisting of:

- 1 4-20 Nm torque spanner, ¼ inch
- 1 100 mm extension, ¼ inch
- 2 150 mm extensions, ¼ inch
- 1 slot for cordless screwdriver, square, ¼ inch
- 1 M6 socket, SW 5, ¼ inch
- 1 M6 socket, 100 mm long with spherical head, ¼ inch



### Advise for use of lubricant GM for HRK 100 and HRK 150:

- HRK 100-SSG-1/18-65:  
Lubricant already included in rubber EPDM. No additional lubrication allowed.
- HRK 100-SSG-4/8-30 as well as HRK 150-SSG-3/24-54 and HRK 150-SSG-6/10-36:  
Lubricant GM incl. in delivery scope.
- HRK 150-SSG-1/36-70 and HRK 150-SSG-1/70-112:  
Please order lubricant GM separately.

## We are here for you.

Whatever your requirements and wishes, we can supply any version to meet your needs.  
Fast and affordable. Contact us! We will be happy to advise you personally.