


Technical data sheet for:

EZA-t 50 / 2K


General data

Item	Splittable sealing element - EZA-t 50 / 2K
Description	For sealing of cable ducts to 0,5 bar, reusable.
Cable diameter	Cables for sealing from 10,5mm till 25,5mm Configuration with one cable: 10,5mm up to 25,5mm Configuration with two cables: sum of both cables = $\leq 30,0$ mm
Package unit	12 Pcs.

Technical data

Quality	Value	Unit
Material	PolyVenylChlorid - Unplastinized PVC-U	
Dimension	d = 50; L = 72;	mm
Pressure	0,5	bar
Pressure after 5 installations	0,5	bar
Tensile strength on PE-Duct	min. 1200	N
Pressing operation clamp on case	min. 1550	N
Fire behavior of case half	E	DIN EN 13501-1
Fire behavior of clamp	E - d2	DIN EN 13501-1

gabocom is certified by the quality system following DIN EN ISO 9001:2008

gabo Systemtechnik GmbH
Am Schaidweg 7
94559 Niederwinkling
Germany

Phone 0049 (0)9962 950 200
Fax 0049 (0)9962 950 202
info@gabocom.de
www.gabocom.de

Editor: LF
Release: MK
Edition: 22.04.2014

No responsibility is taken for the correctness, currency and completeness of details and information.
Liability for damages is excluded.