


Technical data sheet for:

EZA-t 40 / K (Ø 8,0-18,5mm) + 3x10



General data

Item	Splittable sealing element - EZA-t 40 / K (Ø 8,0-18,5mm) + 3x10
Description	For sealing of cable ducts to 0,5 bar, reusable.
Cable diameter	Cable outside diameter from 8,0mm up to 18,5mm
speedpipe	3 Pcs. speedpipe Ø 10mm
Package unit	12 Pcs.

Technical data

Quality	Value	Unit
Material	PolyVenyChlorid - Unplastinized PVC-U	
Dimension	d = 40; L = 72;	mm
Pressure	0,5	bar
Pressure after 5 installations	0,5	bar
Tensile strength on PE-Duct	min. 1000	N
Pressing operation clamp on case	min. 1550	N
Fire behavior of case half	E	DIN EN 13501-1
Fire behavior of clamp	E - d2	DIN EN 13501-1

gabocom is certified by the quality system following DIN EN ISO 9001:2008

gabo Systemtechnik GmbH
 Am Schaidweg 7
 94559 Niederwinkling
 Germany

Phone 0049 (0)9962 950 200
 Fax 0049 (0)9962 950 202
 info@gabocom.de
 www.gabocom.de

Editor: LF
 Release: MK
 Edition: 17.04.2014

No responsibility is taken for the correctness, currency and completeness of details and information.
 Liability for damages is excluded.