


Technical datasheet for:

EZA-t 32 / K



General data

Item	Divisible sealing element - EZA-t 32 / K
Description	For sealing of cable ducts to 0.5 bar, reusable.
Cable diameter	Cable outside diameter from 10.5mm up to 21.5mm.
Package unit	12 Pcs.

Technical data

Quality	Value	Unit
Material	PolyVinylChlorid - Unplastinized PVC-U	
Dimension	d = 32; L = 72	mm
Pressure	0.5	bar
Pressure after 5 installations	0.5	bar
Tensible strength on PE-Duct	min. 1000	N
Pressing operation clamp on case	min. 1550	N
Fire behavior of case half (DIN EN 13501-1)	E	
Fire behavior of clamp (DIN EN 13501-1)	E - d2	

gabocom is certified by the quality system following DIN EN ISO 9001:2008, DIN EN ISO 14001:2004 + Cor 1:2009 and DIN EN 50001:2001. The used materials meet the Reach default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65)

gabo Systemtechnik GmbH
Am Schaidweg 7
94559 Niederwinkling
Germany

Phone 0049 (0)9962 950 200
Fax 0049 (0)9962 950 202
info@gabocom.de
www.gabocom.de

Editor: LF
Release: MK
Date: 07.12.2015
Edition: 2

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.