


Technical datasheet for:

HRMA



General data

Item	Split duct tee, divided
Description	By means of the divided split duct socket tee HRMA speedpipe or cables of a PE/PVC duct can be branched off safely and gas- and water-tight up to 0.5 bar.
Package unit	6 Pcs.

Technical data

Quality	Value	Unit
Material	PolyVinylChlorid - Unplastinized PVC-U	
Dimension	32/32-30°:	d1 = 32; d2 = 32; L = 261
	40/40-90°:	d1 = 40; d2 = 40; L = 261
	50/50-30°:	d1 = 50; d2 = 50; L = 261
	50/50-90°:	d1 = 50; d2 = 50; L = 261
Pressure	0.5	bar
Tensile strength	32/32-30°	min. 1300
	40/40-90°:	min. 1300
	50/50-30°:	min. 1500
	50/50-90°:	min. 1500
Pressing operation clamp on case	min. 1550	N

gabocom is certified by the quality system following DIN EN ISO 9001:2008, DIN EN ISO 14001:2004 + Cor 1:2009 and DIN EN 50001:2001. The used materials meet the Reach default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65)

gabo Systemtechnik GmbH
 Am Schaidweg 7
 94559 Niederwinkling
 Germany

Phone 0049 (0)9962 950 200
 Fax 0049 (0)9962 950 202
 info@gabocom.de
 www.gabocom.de

Editor: LF
 Release: MK
 Date: 07.12.2015
 Edition: 2

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.