


Technical data sheet for:

HRMA



General data

Item	Split duct tee, divided - HRMA 32/32-30°, HRMA 40/40-90°, HRMA 50/50-30°, HRMA 50/50-90°
Description	By means of the divided split duct socket tee HRMA speedpipe or cables of a PE/PVC duct can be branched off safely and gas- and water-tight up to 0,5 bar.
Package unit	6 Pcs.

Technical data

Quality	Value		Unit
Material	PolyVinylChlorid - Unplastinized PVC-U		
Dimension	32/32-30°	d1 = 32; d2 = 32; L = 261;	mm
	40/40-90°	d1 = 40; d2 = 40; L = 261;	
	50/50-30°	d1 = 50; d2 = 50; L = 261;	
	50/50-90°	d1 = 50; d2 = 50; L = 261;	
Pressure	0,5		bar
Tensile strength	32/32-30°	min. 1300	N
	40/40-90°	min. 1300	
	50/50-30°	min. 1500	
	50/50-90°	min. 1500	
Pressing operation clamp on case	min. 1550		N

gabocom is certified by the quality system following DIN EN ISO 9001:2008

gabo Systemtechnik GmbH
Am Schaidweg 7
94559 Niederwinkling
Germany

Phone 0049 (0)9962 950 200
Fax 0049 (0)9962 950 202
info@gabocom.de
www.gabocom.de

Editor: PW
Release: MK
Edition: 14.11.2011

No responsibility is taken for the correctness, currency and completeness of details and information.
Liability for damages is excluded.