


Technical datasheet for:

HRMA 110 / 50 - 30°



General data

Item	Split duct tee, divided
Description	By means of the divided split duct socket tee HRMA speedpipe or cables of a PE/PVC duct can be branched off safely and gas- and water-tight up to 0.5 bar.
Package unit	5 Pcs.

Technical data

Quality	Value	Unit
Material	PolyVinylChlorid - Unplastinized PVC-U	
Dimension	d1 = 110; d2 = 50; L = 300	mm
Pressure	0.5	bar
Pressing operation clamp on case	min. 3250	N

gabocom is certified by the quality system following DIN EN ISO 9001:2008, DIN EN ISO 14001:2004 + Cor 1:2009 and DIN EN 50001:2001. The used materials meet the Reach default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65)

gabo Systemtechnik GmbH
Am Schaidweg 7
94559 Niederwinkling
Germany

Phone 0049 (0)9962 950 200
Fax 0049 (0)9962 950 202
info@gabocom.de
www.gabocom.de

Editor: LF
Release: MK
Date: 07.12.2015
Edition: 2

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.