


Technical datasheet for:

EBM 32, 40 und 50



General data

Item	Divisible connector
Description	Divisible connectors are used for the gas-and watertight sealing of connections between split duct (KKHR) and PE-duct.
Package unit	12 Pcs.

Technical data

Quality	Value		Unit
Material	PolyVinylChlorid - Unplastinized PVC-U		
Dimension	EBM 32:	d = 32; L = 125	mm
	EBM 40:	d = 40; L = 125	
	EBM 50:	d = 50; L = 125	
Pressure	0.5 (permanent gas- and watertight)		bar
	10 / 30		bar / min
Tensile strength	EBM 32:	min. 1300	N
	EBM 40:	min. 1300	
	EBM 50:	min. 1500	
Pressing operation clamp on case	min. 1550		N

gabocom is certified by the quality system following DIN EN ISO 9001:2008, DIN EN ISO 14001:2004 + Cor 1:2009 and DIN EN 50001:2001.

The used materials meet the Reach default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65)

gabo Systemtechnik GmbH
 Am Schaidweg 7
 94559 Niederwinkling
 Germany

Phone 0049 (0)9962 950 200
 Fax 0049 (0)9962 950 202
 info@gabocom.de
 www.gabocom.de

Editor: LF
 Release: MK
 Date: 07.12.2015
 Edition: 2

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.