

Always. Reliable. Tight.

Individual press seal

sealing width 30 mm

HRD50 G 4x12 b30 A2/EPDM55

Individual press seal in closed or split design for sealing new pipes to be installed or pipes that have already been laid. The seal is manufactured according to customer specific dimensional specifications - e.g. eccentric, with covering flange or for multiple and mixed entries.



Picture may differ from selected product

FACTS

Application range:

- DIN 18533 W1.1-E, DIN 18533 W1.2-E, DIN 18533 W2.1-E, DIN 18533 W2.2-E
- Waterproof concrete stress class 1, Waterproof concrete stress class 2

Advantages:

- Manufactured to the millimetre as appropriate for the prevailing installation conditions and in accordance with customer specifications
- Maximum use of space for entries
- Short delivery times

Scope of delivery:

- Lubricating stick

Dimensions:

- Sealing width: 30 mm
- Press plates: 5 mm
- For core drills/wall sleeves \varnothing : 40 mm and higher

Material:

- Press plates, screws, nuts and washers: rust-free stainless steel V2A (AISI 304L), optional V4A (AISI 316L)
- Rubber: EPDM, NBR, KTW or silicone

Tightness:

- Gastight and watertight

FEATURES

Measured inner diameter (D):	50 mm
Split design (G):	G
Number of entries (Z):	4
Measured outer diameter (d):	12 mm
Material:	A2/EPDM55

PICTURES

