


Technical data sheet for:
HRMA


General data

Item	Split duct tee, divided - HRMA 32/32-30°; HRMA 40/4 0-90°; HRMA 50/50-30°; HRMA 50/50-90°
Description	By means of the divided split duct socket tee HRMA speedpipe or cables of a PE/PVC duct can be branched off safely and gas- and water-tight up to 0,5 bar.
Package unit	6 Pcs.

Technical data

Quality	Value	Unit
Material	PolyVenylChlorid - Unplastinized PVC-U	
Dimension	32/32-30°	d1 = 32; d2 = 32; L = 261;
	40/40-90°	d1 = 40; d2 = 40; L = 261;
	50/50-30°	d1 = 50; d2 = 50; L = 261;
	50/50-90°	d1 = 50; d2 = 50; L = 261;
Pressure	0,5	bar
Tensile strength	32/32-30°	min. 1300
	40/40-90°	min. 1300
	50/50-30°	min. 1500
	50/50-90°	min. 1500
Pressing operation clamp on case	min. 1550	N

gabocom is certified by the quality system following DIN EN ISO 9001:2008

gabo Systemtechnik GmbH
 Am Schaidweg 7
 94559 Niederwinkling
 Germany

Phone 0049 (0)9962 950 200
 Fax 0049 (0)9962 950 202
 info@gabocom.de
 www.gabocom.de

Editor: PW
 Release: MK
 Edition: 14.11.2011

No responsibility is taken for the correctness, currency and completeness of details and information.
 Liability for damages is excluded.