


Technical data sheet for:

## EZA-t 12 indoor



### General data

<b>Item</b>	Splittable sealing element indoor - EZA-t indoor
<b>Description</b>	The halogenfree, flame retardant, divisible and tensile sealing element EZA-t indoor is reusable suits for sealing occupied and unoccupied speedpipe for inhouse use. The EZA-t have a safety valve, which opens before reaching 10bar of blow-in pressure. The fire behavior of the hard component is classified according to DIN EN 13501-1.
<b>Package unit</b>	40 pcs.

### Technical data

Quality	Value	Unit
<b>Material</b>		
<b>Material</b>	Polyamid PA flame retardant	
<b>Halogenfree</b>	< 0,02%	DIN EN 60684-2
<b>Fire behavior</b>	B s2 d0	DIN EN 13501-1
<b>Product</b>		
<b>Dimension</b>	d = 28; L = 43	mm
<b>Sealing bend (short term)</b>	EZA-t 12 / 3,0-5,0 indoor	mm
	EZA-t 12 / 5,0-6,5 indoor	
	EZA-t 12 / 6,5-8,0 indoor	
<b>Pressure</b>	0,5	bar
<b>Tensile strength of speedpipe</b>	min. 120	N
<b>Tensile strength to micro-cabel (Ø8,0mm)</b>	min. 60	N
<b>Loading capacity of connecting clamps</b>	min. 750	N

**gabocom is certified by the quality system following DIN EN ISO 9001:2008**

gabo Systemtechnik GmbH  
 Am Schaidweg 7  
 94559 Niederwinkling  
 Germany

Phone 0049 (0)9962 950 200  
 Fax 0049 (0)9962 950 202  
 info@gabocom.de  
 www.gabocom.de

Editor: AF  
 Release: MK  
 Edition: 08.04.2014

No responsibility is taken for the correctness, currency and completeness of details and information.  
 Liability for damages is excluded.