


Technical datasheet for:

EBM indoor



General data

Item	Divisible connector
Description	The halogenfree, flame retardant, tensile and divisible connector EBM indoor ensures the permanent gas- and water-tight connection of occupied speedpipe indoor up to 0.5 bar. Installation is carried out without any special tools. The fire behavior of the hard component is classified according to DIN EN 13501-1.
Package unit	12 Pcs.

Technical data

Quality	Value	Unit
Material		
Material	Polyamid PA flame retardant	
Halogenfree (DIN EN 60684-2)	< 0,02	%
Fire behavior (DIN EN 13501-1)	B s2 d0	
Product		
Dimension	EBM 7 i:	d = 27; L = 88
	EBM 10 i:	d = 28; L = 88
	EBM 12 i:	d = 30; L = 88
	EBM 14 i:	d = 33; L = 88
		mm
Pressure	0.5 / 30	bar / min
Tensile strength	EBM 7 i:	min. 70
	EBM 10 i:	min. 100
	EBM 12 i:	min. 120
	EBM 14 i:	min. 140
		N

**gabocom is certified by the quality system following
DIN EN ISO 9001:2008 and DIN EN ISO 14001:2004 + Cor 1:2009
The used materials meet the Reach default (EU regulation 1907/2006)
and the RoHS default (EU guidelines 2011/65)**

gabo Systemtechnik GmbH
Am Schaidweg 7
94559 Niederwinkling
Germany

Phone 0049 (0)9962 950 200
Fax 0049 (0)9962 950 202
info@gabocom.de
www.gabocom.de

Editor: LF
Release: MK
Date: 08.06.2015
Edition: 1

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.