


Technical datasheet for:



EZA-t 14

General data

Item	Divisible sealing element
Description	The divisible and tensile sealing elements EZA-t are reusable and suit for sealing empty and occupied speedpipe. Before 10 bar of blow-in pressure are reached, the integrated safety valve opens.
Package unit	40 Pcs.

Technical data

Quality	Value	Unit
Material	PolyPhenylenOxid PPO	
Dimension	d = 30; L = 43	mm
Sealing range (short term)	EZA-t 14 / 3.0-5.0	mm
	EZA-t 14 / 5.0-6.5	
	EZA-t 14 / 6.5-8.0	
	EZA-t 14 / 8.0-9.5	
Pressure	0.5	bar
Tensile strength of speedpipe	min. 140	N
Tensile strength to micro-cabel (Ø8.0mm)	min. 60	N
Loading capacity of connecting clamps	min. 750	N
Fire behavior of case half and clamp (DIN EN 13501-1)	E - d2	

gabocom is certified by the quality system following DIN EN ISO 9001:2008, DIN EN ISO 14001:2004 + Cor 1:2009 and DIN EN 50001:2001. The used materials meet the Reach default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65)

gabo Systemtechnik GmbH
Am Schaidweg 7
94559 Niederwinkling
Germany

Phone 0049 (0)9962 950 200
Fax 0049 (0)9962 950 202
info@gabocom.de
www.gabocom.de

Editor: LF
Release: MK
Date: 03.12.2015
Edition: 2

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.