


Technical datasheet for:

**EZA-t 20**


### General data

<b>Item</b>	Divisible sealing element
<b>Description</b>	The divisible and tensile sealing elements EZA-t are reusable and suit for sealing empty and occupied speedpipe. Before 10 bar of blow-in pressure are reached, the integrated safety valve opens.
<b>Package unit</b>	20 Pcs.

### Technical data

Quality	Value	Unit
<b>Material</b>	PolyPhenylenOxid PPO	
<b>Dimension</b>	d = 47; L = 51	mm
<b>Sealing range (short term)</b>	EZA-t 20 / 8.0-10.5	mm
	EZA-t 20 / 10.5-13.0	
<b>Pressure</b>	0.5	bar
<b>Tensile strength of speedpipe</b>	min. 200	N
<b>Tensile strength to micro-cabel (Ø13.0mm)</b>	min. 95	N
<b>Loading capacity of connecting clamps</b>	min. 1550	N
<b>Fire behavior of case half and clamp (DIN EN 13501-1)</b>	E - d2	

**gabocom is certified by the quality system following DIN EN ISO 9001:2008, DIN EN ISO 14001:2004 + Cor 1:2009 and DIN EN 50001:2001. The used materials meet the Reach default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65)**

gabo Systemtechnik GmbH  
 Am Schaidweg 7  
 94559 Niederwinkling  
 Germany

Phone 0049 (0)9962 950 200  
 Fax 0049 (0)9962 950 202  
 info@gabocom.de  
 www.gabocom.de

Editor: LF  
 Release: MK  
 Date: 03.12.2015  
 Edition: 2

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.