


Technical datasheet for:

HEO 7



General data

Item	House lead-in above ground
Description	With the HEO 7 house-connections with speedpipe-ground 7x1.5 can be realized on buildings without cellar. The HEO 7 can be used for a max. wall thickness of 560mm.
Package unit	1 Pcs.

Technical data

Quality	Value	Unit
Material inner part	Polyamid PA flame retardant	
Halogenfree (DIN EN 60684-2)	< 0,02	%
Fire behavior (DIN EN 13501-1)	B s2 d0	
Material outer part	Acrylester-Styrol-Acrylnitril ASA	
Dimension	speedpipe:	7x1.5
	micro-cabel:	0.8 - 4.0
Bending radius speedpipe	inner part	20
	outer part	25
Protection class	splash water protection	IP 65
Pressure	gas-stop longitudinal	0.5 bar
Tensile strenght of speedpipe	min. 70	N
Tensile strength to micro-cable	min. 20	N
Loading capacity of connecting clamps	min. 750	N

gabocom is certified by the quality system following DIN EN ISO 9001:2008, DIN EN ISO 14001:2004 + Cor 1:2009 and DIN EN 50001:2001. The used materials meet the Reach default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65).

gabo Systemtechnik GmbH
Am Schaidweg 7
94559 Niederwinkling
Germany

Phone 0049 (0)9962 950 200
Fax 0049 (0)9962 950 202
info@gabocom.de
www.gabocom.de

Editor: SV
Release: MK
Date: 03.11.17
Edition: 4

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.