


Technical datasheet for:

AdS



General data

Item	Sealing plug	
Description	The sealing plug AdS ensures the gas- and water-tight sealing of insertion ends and sockets up to 0.5 bar.	
Package unit	AdS 50:	20 Pcs.
	AdS 110:	18 Pcs.
	AdS 125:	18 Pcs.

Technical data

Quality	Value	Unit
Material	PolyOxyMethylen POM	
Sealing range	AdS 50:	d = 39.5 - 50.5
	AdS 110:	d = 97.5 - 111
	AdS 125:	d = 116.5 - 126
Pressure	0.5	bar

gabocom is certified by the quality system following DIN EN ISO 9001:2008, DIN EN ISO 14001:2004 + Cor 1:2009 and DIN EN 50001:2001. The used materials meet the Reach default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65)

gabo Systemtechnik GmbH
Am Schaidweg 7
94559 Niederwinkling
Germany

Phone 0049 (0)9962 950 200
Fax 0049 (0)9962 950 202
info@gabocom.de
www.gabocom.de

Editor: LF
Release: MK
Date: 07.12.2015
Edition: 2

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.