

## Technical data sheet for:

## speed·pipe® 10x1,0



General data		
Item	speedpipe 10x1,0	
Description	speedpipe for the use in cable ducts	
Production length on spool (1200x370mm)	2500m	
Weight	approx. 0,030 kg/m	
Total weight	approx. 105 kg (including spool)	

Technical data			
Quality	Value	Unit	
Material			
Material	PolyEthylen PE		
MFI	max. 30	%	
Homogeneity	free from inclusions < 0,02	mm <sup>2</sup>	
Internal pressure creep rupture test	Sigma 4,0 for 170h at 80°C	N/mm <sup>2</sup>	
Fire behavior	E	DIN EN 13501-1	
speedpipe 10x1,0			
Dimension	$D = 10,0^{+0,1}$ ; $s = 1,0^{+0,1}$	mm	
Colour of stripes	red, green, blue, yellow, white, grey and orange opposite transparent windows		
Pressure nominal	PN 10		
Inner surface	63 optimized sliding ribs		
Burst pressure	min. 30	bar at 20°C	
Max. pull strength	150	N	
Elongiation from pulling force	220	N	
Break at pulling force	450	N	

## gabocom is certified by the quality system following DIN EN ISO 9001:2008

gabo Systemtechnik GmbH Phone 0049 (0)9962 950 200 Editor: LF
Am Schaidweg 7 Fax 0049 (0)9962 950 202 Release: MK
94559 Niederwinkling info@gabocom.de Edition: 27.05.2014

Germany www.gabocom.de

No responsibility is taken for the correctness, currency and completeness of details and information. Liability for damages is excluded.