


Technical data sheet for:

## EZA-t 32,40,50 and 63



### General data

<b>Item</b>	Splittable sealing element - EZA-t 32, EZA-t 40, EZA-t 50, EZA-t 63
<b>Description</b>	To seal the space between speedpipe and PE- or coat duct till 0,5 bar. Even for ducts temporary without speedpipe, reusable
<b>Package unit</b>	12 Pcs.

### Technical data

Quality	Value	Unit
<b>Material</b>	PolyVinylChlorid - Unplastinized PVC-U	
<b>Dimension</b>	EZA-t 32: d = 32; L = 72;	mm
	EZA-t 40: d = 40; L = 72;	
	EZA-t 50: d = 50; L = 72;	
	EZA-t 63: d = 63; L = 72;	
<b>Pressure</b>	0,5	bar
<b>Pressure after 5 installations</b>	0,5	bar
<b>Tensile strength</b>	from PE-duct:	N
	min. 1.000 (Ø32 & 40) & 1.200 (Ø50 & 63))	
	from speedpipe-bundle:	
	min. 420 (Ø32)	
	min. 550 (Ø40)	
	min. 700 (Ø50)	
	min. 900 (Ø63)	
<b>Tensile strength on speedpipe</b>	min. 50	N
<b>Pressing operation clamp on case</b>	min. 1550	N
<b>Fire behavior of case half</b>	E	DIN EN 13501-1
<b>Fire behavior of clamp</b>	E - d2	DIN EN 13501-1

**gabocom is certified by the quality system following DIN EN ISO 9001:2008**

gabo Systemtechnik GmbH  
Am Schaidweg 7  
94559 Niederwinkling  
Germany

Phone 0049 (0)9962 950 200  
Fax 0049 (0)9962 950 202  
info@gabocom.de  
www.gabocom.de

Editor: LF  
Release: MK  
Edition: 17.04.2014

No responsibility is taken for the correctness, currency and completeness of details and information.  
Liability for damages is excluded.