


Technical data sheet for:

EZA-t 10



General data

Item	Splittable seling element - EZA-t 10
Description	The divisible and tensile sealing element EZA-t is reusable suits for sealing occupied and unoccupied speedpipe. The EZA-t have a safety valve, which opens before reaching 10bar of blow-in pressure.
Package unit	40 Pcs.

Technical data

Quality	Value	Unit
Material	PolyPhenylenOxid PPO	
Dimension	d = 27; L = 43	mm
Sealing bend (short term)	EZA-t 10 / 1,8-3,5	mm
	EZA-t 10 / 3,0-5,0	
	EZA-t 10 / 5,0-6,5	
Pressure	0,5	bar
Tensile strength of speedpipe	min. 100	N
Tensile strength to micro-cabel (Ø6,5mm)	min. 50	N
Loading capacity of connecting clamps	min. 750	N
Fire behavior of case half and clamp	E - d2	DIN EN 13501-1

gabocom is certified by the quality system following DIN EN ISO 9001:2008

gabo Systemtechnik GmbH
 Am Schaidweg 7
 94559 Niederwinkling
 Germany

Phone 0049 (0)9962 950 200
 Fax 0049 (0)9962 950 202
 info@gabocom.de
 www.gabocom.de

Editor: LF
 Release: MK
 Edition: 17.04.2014

No responsibility is taken for the correctness, currency and completeness of details and information.
 Liability for damages is excluded.