


Technical datasheet for:
KKHRB 50

General data

Item	Split duct bend - KKHRB 50 type I; KKHRB type II		
Description	The divided split duct bend is used for repairing ducts that are laid in a bend due to changes of the pipe way or due to height differences. It consist of PVC-U and is gas- and water-tight up to 0,5 bar.		
Optional	To install the spilt ducts, it is necessary to use the according assembly tool.		
Package unit	1 Pc. / VE		
Chord length	KKHRB 50 type I (90°):	1379 ^{+/-40} mm	
	KKHRB 50 type II (45°):	2776 ^{+/-40} mm	

Technical data

Quality	Value	Unit
Material	PolyVenylChlorid - Unplastinized PVC-U	
Dimension	d = 50,0 ^{+0,2} ; s = 2,4 ^{+0,5}	mm
Pressure	0,5 (permanent gas- and watertight)	bar
	10 / 30	bar / min
	mastic (enclosed at the sleeves) is to use according installation instruction	

gabocom is certified by the quality system following DIN EN ISO 9001:2008

gabo Systemtechnik GmbH
 Am Schaidweg 7
 94559 Niederwinkling
 Germany

Phone 0049 (0)9962 950 200
 Fax 0049 (0)9962 950 202
 info@gabocom.de
 www.gabocom.de

Editor: SV
 Release: MK
 Edition: 14.11.14

No responsibility is taken for the correctness, currency and completeness of details and information.
 Liability for damages is excluded.