


Technical data sheet for:

## EZA-t 10



### General data

<b>Item</b>	Splittable seling element - EZA-t 10
<b>Description</b>	The divisible and tensile sealing element EZA-t is reusable suits for sealing occupied and unoccupied speedpipe. The EZA-t have a safety valve, which opens before reaching 10bar of blow-in pressure.
<b>Package unit</b>	40 Pcs.

### Technical data

Quality	Value	Unit
<b>Material</b>	PolyPhenylenOxid PPO	
<b>Dimension</b>	d = 27; L = 43	mm
<b>Sealing bend (short term)</b>	EZA-t 10 / 1,8-3,5	mm
	EZA-t 10 / 3,0-5,0	
	EZA-t 10 / 5,0-6,5	
<b>Pressure</b>	0,5	bar
<b>Tensile strength of speedpipe</b>	min. 100	N
<b>Tensile strength to micro-cabel (Ø6,5mm)</b>	min. 50	N
<b>Loading capacity of connecting clamps</b>	min. 750	N

**gabocom is certified by the quality system following DIN EN ISO 9001:2008**

gabo Systemtechnik GmbH  
 Am Schaidweg 7  
 94559 Niederwinkling  
 Germany

Phone 0049 (0)9962 950 200  
 Fax 0049 (0)9962 950 202  
 info@gabocom.de  
 www.gabocom.de

Editor: PW  
 Release: MK  
 Edition: 15.11.2011

No responsibility is taken for the correctness, currency and completeness of details and information.  
 Liability for damages is excluded.