


Technical data sheet for:

KKHR 110 und 125



General data			
Item	Split duct, KKHR 110 und 125		
Description	Consists of 2 half shells, for pressure tight repair damages in cable ducts in combination with KKHRM.		
Optional	To install the split ducts, it is necessary to use the according assembly tool.		
Package unit	KKHR Ø 110mm x 2000mm:	3 pieces / unit; 78 pieces / pallet	
	KKHR Ø 110mm x 6000mm:	3 pieces / unit; 78 pieces / pallet	
	KKHR Ø 125mm x 3000mm:	4 pieces / unit; 52 pieces / pallet	
	KKHR Ø 125mm x 6000mm:	4 pieces / unit; 52 pieces / pallet	
Production length	KKHR 110: 2000 / 6000 m	2000 / 6000 mm	
	KKHR 125: 3000 / 6000 m	: 3000 / 6000 mm	

Technical data			
Quality	Value	Unit	
Material	PolyVenylChlorid - Unplastinized PVC-U		
Dimension	$d = 110,0^{+0,3}$; $s = 3,2^{+0,5}$	mm	
	$d = 125,0^{+0,3}$; $s = 3,7^{+0,6}$		
Pressure	0,5 (permanent gas- and watertight)	bar	
	mastic (enclosed at the sleeves) is to use according installation instruction		

gabocom is certified by the quality system following DIN EN ISO 9001:2008

gabo Systemtechnik GmbH Phone 0049 (0)9962 950 200 Editor: PW
Am Schaidweg 7 Fax 0049 (0)9962 950 202 Release: MK
94559 Niederwinkling info@gabocom.de Edition: 15.11.2011

Germany www.gabocom.de

No responsibility is taken for the correctness, currency and completeness of details and information. Liability for damages is excluded.