


Technical data sheet for:
EBM


General data

Item	Divisible connector - EBM EBM 7; EBM 10; EBM 12; EBM 14; EBM 16
Description	The tensile and divisible connector EBM ensures the permanent gas- and water-tight connection of occupied speedpipe up to 0,5 bar and for a duration of 30 minutes even up to 10 bar. Installation is carried out without any special tools.
Package unit	12 pcs.

Technical data

Quality	Value	Unit
Material	PolyPhenylenOxid PPO	
Dimension	EBM 7: d = 27; L = 88	mm
	EBM 10: d = 28; L = 88	
	EBM 12: d = 30; L = 88	
	EBM 14: d = 33; L = 88	
	EBM 16: d = 36; L = 92	
Pressure	0,5 (permanent gas- and watertight)	bar
	10 / 30	bar / min
Tensile strength	EBM 7: min. 70	N
	EBM 10: min. 100	
	EBM 12: min. 120	
	EBM 14: min. 140	
	EBM 16: min. 160	
Loading capacity of connecting clamps	min. 750	N
Fire behavior of case half and clamp	E - d2	DIN EN 13501-1

gabocom is certified by the quality system following DIN EN ISO 9001:2008

gabo Systemtechnik GmbH
Am Schaidweg 7
94559 Niederwinkling
Germany

Phone 0049 (0)9962 950 200
Fax 0049 (0)9962 950 202
info@gabocom.de
www.gabocom.de

Editor: LF
Release: MK
Edition: 17.04.2014

No responsibility is taken for the correctness, currency and completeness of details and information.
Liability for damages is excluded.