


Technical data sheet for:

EBM-GS 10



General data

Item	Divisible connector with gas-stop - EBM-GS EBM-GS 10 / 1,8-3,5; EBM-GS 10 / 3,0-5,0; EBM-GS 10 / 5,0-6,5
Description	The divisible connector EBM-GS is furnished with an integrated gas-stop, with it can connect occupied and unoccupied speedpipe and seal longitudinally.
Package unit	12 Pcs.

Technical data

Quality	Value	Unit
Material	PolyPhenylenOxid PPO	
Dimension	d = 29; L = 88	mm
Sealing bend (short term)	EBM-GS 10 / 1,8-3,5	mm
	EBM-GS 10 / 3,0-5,0	
	EBM-GS 10 / 5,0-6,5	
Pressure	0,5	bar
Tensile strength of speedpipe	min. 100	N
Tensile strength of micro-cabel (Ø6,5mm)	min. 50	N
Loading capacity of connecting clamps	min. 750	N
Fire behavior of case half and clamp	E - d2	DIN EN 13501-1

gabocom is certified by the quality system following DIN EN ISO 9001:2008

gabo Systemtechnik GmbH
Am Schaidweg 7
94559 Niederwinkling
Germany

Phone 0049 (0)9962 950 200
Fax 0049 (0)9962 950 202
info@gabocom.de
www.gabocom.de

Editor: LF
Release: MK
Edition: 17.04.2014

No responsibility is taken for the correctness, currency and completeness of details and information.
Liability for damages is excluded.