


Technical datasheet for:

## EZA-t 12



### General data

<b>Item</b>	Splittable seling element - EZA-t 12
<b>Description</b>	The divisible and tensile sealing element EZA-t is reusable suits for sealing occupied and unoccupied speedpipe. The EZA-t have a safety valve, which opens before reaching 10bar of blow-in pressure.
<b>Package unit</b>	40 Pcs.

### Technical data

Quality	Value	Unit
<b>Material</b>	PolyPhenylenOxid PPO	
<b>Dimension</b>	d = 28; L = 43	mm
<b>Sealing bend (short term)</b>	EZA-t 12 / 3,0-5,0	mm
	EZA-t 12 / 5,0-6,5	
	EZA-t 12 / 6,5-8,0	
<b>Pressure</b>	0,5	bar
<b>Tensile strength of speedpipe</b>	min. 120	N
<b>Tensile strength to micro-cabel (Ø8,0mm)</b>	min. 60	N
<b>Loading capacity of connecting clamps</b>	min. 750	N
<b>Fire behavior of case half and clamp</b>	E - d2	DIN EN 13501-1

**gabocom is certified by the quality system following DIN EN ISO 9001:2008**

gabo Systemtechnik GmbH  
Am Schaidweg 7  
94559 Niederwinkling  
Germany

Phone 0049 (0)9962 950 200  
Fax 0049 (0)9962 950 202  
info@gabocom.de  
www.gabocom.de

Editor: LF  
Release: MK  
Edition: 17.04.2014

No responsibility is taken for the correctness, currency and completeness of details and information.  
Liability for damages is excluded.