


Technical datasheet for:

EZA-t 32,40,50 and 63



General data

Item	Splittable sealing element - EZA-t 32, EZA-t 40, EZA-t 50, EZA-t 63
Description	To seal the space between speedpipe and PE- or coat duct till 0,5 bar. Even for ducts temporary without speedpipe, reusable
Package unit	12 Pcs.

Technical data

Quality	Value	Unit
Material	PolyVenylChlorid - Unplastinized PVC-U	
Dimension	EZA-t 32: d = 32; L = 72;	mm
	EZA-t 40: d = 40; L = 72;	
	EZA-t 50: d = 50; L = 72;	
	EZA-t 63: d = 63; L = 72;	
Pressure	0,5	bar
Pressure after 5 installations	0,5	bar
Tensile strength	from PE-duct:	N
	min. 1.000 (Ø32 & 40) & 1.200 (Ø50 & 63))	
	from speedpipe-bundle:	
	min. 420 (Ø32)	
	min. 550 (Ø40)	
	min. 700 (Ø50)	
	min. 900 (Ø63)	
Tensile strength on speedpipe	min. 50	N
Pressing operation clamp on case	min. 1550	N
Fire behavior of case half	E	DIN EN 13501-1
Fire behavior of clamp	E - d2	DIN EN 13501-1

gabocom is certified by the quality system following DIN EN ISO 9001:2008

gabo Systemtechnik GmbH
Am Schaidweg 7
94559 Niederwinkling
Germany

Phone 0049 (0)9962 950 200
Fax 0049 (0)9962 950 202
info@gabocom.de
www.gabocom.de

Editor: LF
Release: MK
Edition: 17.04.2014

No responsibility is taken for the correctness, currency and completeness of details and information.
Liability for damages is excluded.