


Technical datasheet for:

EZA-t tc



General Data

Item	Divisible sealing element for SRV-G tc
Description	The reusable EZA-t tc are suitable for sealing tc-speedpipe bundles (tight covered) without loose outer jacket and up to 0.5 bar pressure tight.
Package unit	12 Pcs.

Technical Data

Quality	Value	Unit
Material	PolyVinylChlorid - Unplastinized PVC-U	
Dimension	L = 72	mm
Pressure	0.5	bar
Pressure after 5 installations	0.5	bar
Tensile strength of speedpipe bundles	250	N
Tensile strength of micro tubes	≥ 50	N
Pressing operation clamp on case	min. 1550	N
Fire behavior of case half (DIN EN 13501-1)	E	
Fire behavior of clamp (DIN EN 13501-1)	E - d2	

gabocom is certified by the quality system following DIN EN ISO 9001:2008, DIN EN ISO 14001:2004 + Cor 1:2009 and DIN EN 50001:2001. The used materials meet the Reach default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65)

gabo Systemtechnik GmbH
Am Schaidweg 7
94559 Niederwinkling
Germany

Phone 0049 (0)9962 950 200
Fax 0049 (0)9962 950 202
info@gabocom.de
www.gabocom.de

Editor: LF
Release: MK
Date: 08.03.2016
Edition: 3

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.