


Technical datasheet for:



## RSM transparent permanent

### General data

<b>Item</b>	Reducer transparent permanent RSM 12/10; RSM 14/12
<b>Description</b>	The transparent, permanent reducers RSM are used for the gas- and water-tight connection of speed•pipe® with the same inner diameter up to 15 bar. They can easily and fastly be installed. By removing the locking ring they can easily be disengaged. The fittings are applicable for direct burying.
<b>Package unit</b>	25 pcs.

### Technical data

Quality	Value	Unit
<b>Material</b>	PolyAmid PA	
<b>Dimension</b>	RSM 12/10: d = 23; L = 46	mm
	RSM 14/12: d = 23; L = 46	
<b>Pressure</b>	0,5 (permanent gas- and watertight)	bar
	15/30	bar/min
<b>Burst pressure</b>	min. 30	bar
<b>Tensile strenght</b>	RSM 12/10: min. 400	N
	RSM 14/12: min. 450	
<b>Fire behavior of corpus</b>	E - d2	DIN EN 13501-1

**gabocom is certified by the quality system following DIN EN ISO 9001:2008**

gabo Systemtechnik GmbH  
Am Schaidweg 7  
94559 Niederwinkling  
Germany

Phone 0049 (0)9962 950 200  
Fax 0049 (0)9962 950 202  
info@gabocom.de  
www.gabocom.de

Editor: LF  
Release: MK  
Edition: 23.04.2014

No responsibility is taken for the correctness, currency and completeness of details and information.  
Liability for damages is excluded.