

_					•
IAC	hnica	ลเ ตล	TASD	PPT	\mathbf{ror}





General data					
Item	Protective cap SK				
Description	The Protective cap SK is used for closing speedpipe against dirt.				
Package unit	100 Pcs.				

Technical data							
Quality	Value		Unit				
Material	PolyEthylen PE						
	SK 7:	d = 7; L = 18,6					
	SK 10:	d = 10; L = 18,6					
	SK 12:	d = 12; L = 18,5					
Dimension	SK 14:	d = 14; L = 18,6	mm				
Dillielision	SK 16:	d = 16; L = 19,8	mm				
	SK 18:	d = 18; L = 20					
	SK 20:	d = 20; L = 20					
	SK 25:	d = 25; L = 50					

d = speedpipe-diameter

gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001.

The used materials meet the REACH default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65).

gabo Systemtechnik GmbH Am Schaidweg 7 94559 Niederwinkling GERMANY Tel. +49 9962 950-200 Fax +49 9962 950-202 info@gabocom.com www.gabocom.com Editor: LF Release: MK Date: 04.12.2015

Edition: 2

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.