

Technical data sheet for:

EBM-GS 7



General data		
Item	Divisable connector with gas-stop - EBM-GS EBM-GS 7 / 0,8-4,0	
Description	The divisible connector EBM-GS is furnished with an integrated gas-stop, with it can connect occupied and unoccupied speedpipe and seal longitudinally.	
Package unit	12 Pcs.	

Technical data			
Quality	Value	Unit	
Material	PolyPhenylenOxid PPO		
Dimension	d = 28; L = 88	mm	
Sealing bend (short term)	EBM-GS 7 / 0,8-4,0	mm	
Pressure	0,5	bar	
Tensile strength of speedpipe	min. 70	N	
Tensile strength to micro-cabel (Ø4,0mm)	min. 20	N	
Loading capacity of connecting clamps	min. 750	N	
Fire behavior of case half and clamp	E - d2	DIN EN 13501-1	

gabocom is certified by the quality system following DIN EN ISO 9001:2008

gabo Systemtechnik GmbH Phone 0049 (0)9962 950 200 Editor: LF
Am Schaidweg 7 Fax 0049 (0)9962 950 202 Release: MK
94559 Niederwinkling info@gabocom.de Edition: 17.04.2014

Germany www.gabocom.de

No responsibility is taken for the correctness, currency and completeness of details and information. Liability for damages is excluded.