


Technical data sheet for:

EZA-t 14 indoor



General data

Item	Splittable sealing element indoor - EZA-t 14 indoor
Description	The halogenfree, flame retardant, divisible and tensile sealing element EZA-t indoor is reusable suits for sealing occupied and unoccupied speedpipe for inhouse use. The EZA-t have a safety valve, which opens before reaching 10bar of blow-in pressure. The fire behavior of the hard component is classified according to DIN EN 13501-1.
Package unit	40 pcs.

Technical data

Quality	Value	Unit
Material		
Material	Polyamid PA flame retardant	
Halogenfree	< 0,02%	DIN EN 60684-2
Fire behavior	B s2 d0	DIN EN 13501-1
Product		
Dimension	d = 30; L = 43	mm
Sealing bend (short term)	EZA-t 14 / 3,0-5,0 indoor	mm
	EZA-t 14 / 5,0-6,5 indoor	
	EZA-t 14 / 6,5-8,0 indoor	
	EZA-t 14 / 8,0-9,5 indoor	
Pressure	0,5	bar
Tensile strength of speedpipe	min. 140	N
Tensile strength to micro-cabel (Ø8,0mm)	min. 60	N
Loading capacity of connecting clamps	min. 750	N

gabocom is certified by the quality system following DIN EN ISO 9001:2008

gabo Systemtechnik GmbH
 Am Schaidweg 7
 94559 Niederwinkling
 Germany

Phone 0049 (0)9962 950 200
 Fax 0049 (0)9962 950 202
 info@gabocom.de
 www.gabocom.de

Editor: AF
 Release: MK
 Edition: 08.04.2014

No responsibility is taken for the correctness, currency and completeness of details and information.
 Liability for damages is excluded.