


Technical datasheet for:



EZA-t 14

General data

Item	Splittable seling element - EZA-t 14
Description	The divisibile and tensile sealing element EZA-t is reusable suits for sealing occupied and unoccupied speedpipe. The EZA-t have a safety valve, which opens before reaching 10bar of blow-in pressure.
Package unit	40 Pcs.

Technical data

Quality	Value	Unit
Material	PolyPhenylenOxid PPO	
Dimension	d = 30; L = 43	mm
Sealing bend (short term)	EZA-t 14 / 3,0-5,0	mm
	EZA-t 14 / 5,0-6,5	
	EZA-t 14 / 6,5-8,0	
	EZA-t 14 / 8,0-9,5	
Pressure	0,5	bar
Tensile strength of speedpipe	min. 140	N
Tensile strength to micro-cabel (Ø8,0mm)	min. 60	N
Loading capacity of connecting clamps	min. 750	N
Fire behavior of case half and clamp	E - d2	DIN EN 13501-1

gabocom is certified by the quality system following DIN EN ISO 9001:2008

gabo Systemtechnik GmbH
Am Schaidweg 7
94559 Niederwinkling
Germany

Phone 0049 (0)9962 950 200
Fax 0049 (0)9962 950 202
info@gabocom.de
www.gabocom.de

Editor: LF
Release: MK
Edition: 17.04.2014

No responsibility is taken for the correctness, currency and completeness of details and information.
Liability for damages is excluded.