ROBUS°

EMERGENCY

LED EMERGENCY EXIT BOX

4W. IP20



3^{YRS} WARRANTY









OP 220 240 OPERATING VOLTAGE





CONSTRUCTION

FEATURES

Polystyrene diffuserLiFePO₄ battery

automated unit



PRODUCT INFORMATION DOCUMENT

Pressed steel, powder coated housing

 Large, high contrast legends providing maximum viewing distance of 30m
 Self-test plug and play module available turning the fitting into fully

 High quality LiFePO₄ battery have increased reliability over commonly used NiCad and NiMH batteries
 Complete with running man legend with arrow up or down, other legends

available as accessories






LIFETIME TEXT	
Arrow UP	R8EMLP4U-01
Arrow DOWN	R8EMLP4D-01
Comparable to:	8W T4
Total Power (W):	3.8
Total Light Output (lm):	40
Total Emergency Light Output (lm):	15
Efficacy (lm/cctW):	11
Lux at 1m (lux):	5
Emergency Lux at 1m (lux):	2
CCT (K):	6,500
CRI:	70
IP:	20
Operation Temperature (°C):	0 ≤ Ta ≤ +40
Inrush Current:	5A/1ms
RG Value:	0
Rated Life to L70B50 (Hrs):	54,000
Dimensions LxWxH:	390x192x60
Weight (kg):	1.2

Product is certified to all the relevant standards.

Please contact our technical department for market specific compliances.

ACCESSORIES:

REMSTU	Plug and Play Self-Test Module
R8EMD	EXIT BOX spare running man legend DOWN
R8EML	EXIT BOX spare running man legend LEFT
R8EMR	EXIT BOX spare running man legend RIGHT
R8EMU	EXIT BOX spare running man legend UP






Diagram for R8EMLP4D-01 in Maintained Mode. Other diagrams available on request

PLEASE NOTE: INFORMATION IN THIS DOCUMENT MAY BE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

IRE: TEL: +353 1 709 9000
UK: TEL: 0800 973 220
AUS: TEL: +61 7 3890 5444
NZ: TEL: +64 03 668 5285

WEB: WWW.ROBUS.COM WEB: WWW.ROBUS.COM WEB: WWW.ROBUS.COM.AU WEB: WWW.ROBUSLED.CO.NZ