

ROBUS®

FLEXI-STRIPS

ATLANTIC AC STRIP

8W/m, IP65



PRODUCT INFORMATION DOCUMENT

FEATURES

- Full PVC construction with IP65 rating and high UV resistance making it suitable for indoor and outdoor applications
- Driverless design with on-board constant current IC driver and rectifier for direct 220-240V AC power supply– no need for additional drivers
- Passes EMC class C harmonics at wattages >25W
- Over-voltage, over-current and over temperature protection with on-board IC driver
- Maximum run length of 50m with cut points every 20cm
- Available through the Cut to Length service offered by the Robus Conversions team

CONSTRUCTION

- Full PVC construction



WARRANTY



LUMINAIRE LIFETIME



LUMENS PER W



IK RATING



IP RATING



OPERATING VOLTAGE



BEAM ANGLE



DIMMING



CCT



SAFETY CLASS

Product Code:	RAA8306550	RAA8406550
Comparable to:	NA	NA
Total Power (W):	8.3	8.1
Power Factor:	0.5	0.5
Total Light Output (lm):	840	850
Total Emergency Light Output (lm):	NA	NA
Efficacy (lm/cctW):	101	105
Lux at 1m (lux):	320	330
Emergency Lux at 1m (lux):	NA	NA
CCT (K):	3000	4000
CRI:	80	80
IP:	65	65
Operation Temperature (°C):	-20 ≤ Ta ≤ +40	-20 ≤ Ta ≤ +40
Inrush Current:	1.32A/0.1us/m	1.32A/0.1us/m
RG Value:	0	0
SDCM:	<6	<6
P _{ST} LM:	0.06	0.06
SVM:	4.5	4.5
Energy Class:	E	E
Rated Life to L70B50 (Hrs):	30000	30000
Dimensions ØxH (mm):	5000x17x7	5000x17x7
Weight (kg):	6.9	6.9

Separate Control Gear Information

Type of Light Source:	NA	NA
Full Load Efficiency (%):	NA	NA
P _{NET} (W):	NA	NA
Dimensions (mm):	NA	NA

Product is certified to all the relevant standards.

Please contact our technical department for market specific compliances.

PLEASE NOTE: INFORMATION IN THIS DOCUMENT MAY BE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

IRE: TEL: +353 1 709 9000
 UK: TEL: 0800 973 220
 AUS: TEL: +61 7 3890 5444
 NZ: TEL: +64 03 668 5285

WEB: ROBUS.COM
 WEB: ROBUS.COM
 WEB: ROBUS.COM.AU
 WEB: ROBUSLED.CO.NZ

LED GROUP EUROPE · UK · AUSTRALIA · NEW ZEALAND · ASIA · MIDDLE EAST · AFRICA

ATLANTIC AC STRIP

8W/m, IP65

Cone Illuminance Diagram





Diagram for RAA8406550 in 4000K. Other diagrams available on request

Dimension Diagram



Sensor Data

Time Off Delay:	NA
NA Illuminance Switching Range:	NA
Sensitivity Range (%):	NA
Mounting Height (max):	NA
Detection Zone Diameter (max):	NA

Polar Intensity Diagram




Diagram for RAA8406550 in 4000K. Other diagrams available on request

Accessories

RAAC	Strip-to-Strip Connector
RAAC15	Strip-to-Strip Connector With 150mm cable
RAAC30	Strip-to-Strip Connector With 300mm cable
RAAB	Mounting Bracket
RAAIC	1500mm Input Cable With Fuse
RAAG	Glue
RAAEC	End Cap