

CHAMPION 30W LED FLOOD LIGHT IP65, BLACK, 4000K

RCM3040-04

PLEASE READ INSTRUCTION BEFORE COMMENCING INSTALLATION AND RETAIN FOR FUTURE REFERENCES.

! Electrical products can cause death or injury, or damage to property. If in any doubt about the installation or use of this product, consult a competent electrician

Note:

Product technical information and specification may change over time without prior notification. For the latest technical information please visit our web site www.ledgrouprobust.com or robustdirect.com

-20°C < Ta < +40°C, 220-240V ~ 50/60Hz, Class I, IP65
Luminaire is non-dimmable

Installation

1. Ensure mains supply is switched off before commencing work.
 2. Select suitable location for luminaire.
 3. Remove bracket from luminaire, mark wall with appropriate fixing positions. Before drilling, ensure that the hole does not impinge on pipe work, cables or other building services.
 4. Mount bracket on wall and re-attach luminaire. Adjust to desired angle.
 5. The luminaire is supplied with 1m of rubber cable. Using suitable IP rated enclosure terminate Brown (Live), Blue (Neutral) and Green/ Yellow (Earth) to switch supply.
 6. This product has no user serviceable parts. If any part is damaged, disconnect from mains and discontinue use.
- Note: No "fixings screws provided", please use appropriate fixings screws.

Warning: ensure all screws are completely tightened before use

Projection Distance: 6m – 12m
Max Projection Area: 12m x 16m
Mounting Height: 2.5m – 4m

The Installation must be carried out by a qualified electrician

LED Group Australasia
9/210 Queensport Road North
Murarrie
QLD 4172
Australia

Tel: +61 7 3890 5444
Fax: +61 7 3890 4777
Email: purchases@ledgrouprobust.com.au
Website: www.ledgrouprobust.com.au

