ROBUS°

DOWNLIGHTS

CAPELLA GU10 Fire Rated Downlight

IP20/65



PRODUCT INFORMATION DOCUMENT

FEATURES

- Modern open back design for improved lamp cooling and performance
- Universal can size across all bezel types for stock saving and retro fit change flexibility
- Quick fit loop-in, loop-out push in terminals and cable clamp
- Tested for use with I-Joists & Metal Web Joists

CONSTRUCTION

- Steel body and glass lens with intumescent seal providing security of passive and active fire barrier protection
- 30 and 60-minute certified GU10 lamp holder and fire rated downlight in IP65/20 fixed and IP20 directional versions
- Reversible terminal block cover assembly to accommodate low profile ceilings
- Compliant to Building Regulations Part B, C & E





















CLASS RCPF10 EU/1/ F

Comparable to:	50W halogen
Total Power (W):	XXX
Total Light Output (lm):	XXX
Total Emergency Light Output (Im):	NA
Efficacy (lm/cctW):	XXX
IP:	20/65
Operation Temperature (°C)	-20 ≤ Ta ≤ +40
Lux at 1m (lux):	XXX
Emergency Lux at 1m (lux):	NA
Inrush Current:	XXX
CCT (K):	XXX
RG Value:	XXX
Rated Life to L70B50 (Hrs):	XXX
Dimensions ØxH (mm):	90x114
Cut Out (mm):	73-78
Weight (kg):	0.13

xxx - Actual performance depends on the lamp used

ACCESSORIES:

RCPFIG Insulation Guard RCPFB20S-01/03/13 IP20 Bezel, Straight RCPFB20D-01/03/13 IP20 Bezel, Directional RCPFB65S-01/03/13 IP65 Bezel, Straight RCPFB65D-01/03/13 IP65 Bezel, Directional

White -01 -03 Chrome -13 Brushed Chrome

RCPFIG 136.5mm Ø90mm







Product is certified to all the relevant standards.

Please contact our technical department for market specific compliances