

ROBUS®

INDUSTRIAL

FALCON WALL LIGHT, 5500K, BLACK

35W, 50W, IP65





PRODUCT INFORMATION DOCUMENT

CONSTRUCTION

- Die cast aluminium powder-coated housing
- Polycarbonate diffuser
- High quality SMD LED's

FEATURES



- Die cast aluminium housing providing optimal heat dissipation and high resistance to weather conditions
- Prewired with 1.5m of rubber flex for easy, quick installation
- Emergency and sensor options available through our Emergency Conversions Unit



Standard Photocell	RHA03555-04 RHA03555DH-04	RHA05055-04 RHA05055DH-04
Comparable to:	200W halogen	350W halogen
Total Power (W):	31.1	53.2
Total Light Output (lm):	3,240	5,380
Total Emergency Light Output (lm):	NA	NA
Efficacy (lm/cctW):	104	101
Lux at 1m (lux):	410	1,040
Emergency Lux at 1m (lux):	NA	NA
CCT (K):	5,500	5,500
CRI:	80	80
IP:	65	65
Operation Temperature (°C):	-20 ≤ Ta ≤ +40	-20 ≤ Ta ≤ +40
Inrush Current:	34A/3.6us	36A/3.6us
RG Value:	0	0
Dimensions LxWxH:	300x265x180	300x265x180
Weight (kg):	3.0	3.04

Product is certified to all the relevant standards.

Please contact our technical department for market specific compliances.



PLEASE NOTE: INFORMATION IN THIS DOCUMENT MAY BE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

IRE: TEL: +353 1 709 9000
UK: TEL: 0800 973 220
AUS: TEL: +61 7 3890 5444
NZ: TEL: +64 03 668 5285

WEB: WWW.ROBUS.COM
WEB: WWW.ROBUS.COM
WEB: WWW.ROBUS.COM.AU
WEB: WWW.ROBUSLED.CO.NZ

LED GROUP EUROPE · AUSTRALIA · NEW ZEALAND · ASIA · MIDDLE EAST · AFRICA

Diagram for RFA03555-04. Other diagrams available on request