


OUTDOOR

FALCON IP65 LED WALL PACK



This attractive high quality wall pack utilises the latest energy efficient Chip on Board LED's to provide tremendous light output whilst using minimum electricity and is maintenance free. Energy savings are further optimised using microwave or photocell versions

Huge savings can be made compared to traditional light sources which use high-pressure sodium, metal halide (MH), or incandescent lamps.

Wall-packs are widely used to provide perimeter, accent, amenity and security lighting in:

- Indoor parking areas
- Tunnels
- Walkways
- Building entrances
- Loading bays
- Recreational areas
- Fire assembly points

| | |
|--|----------------------------------|
| Order Codes | Standard: RFA05055X-04 |
| | Photocell: RFA05055DHX-04 |
| | Microwave: RFA05055DMX-04 |
| Comparable to MH/Halogen: | 80/350 |
| Total Power Consumed (W): | 49.6 |
| Total Light Output (lm): | 3,380 |
| Efficacy (Lm/cctW): | 68 |
| Illuminance @1m (lx): | 650 |
| Beam Angle (Deg): | 120 |
| Correlated Colour Temp (CCT): | 5500 |
| Colour Rendering Index (Ra): | 75 |
| Warranty (yrs): | 3 |
| Rated LED Life (hrs): | 30,000 |
| Operating temperature range (°C): | -25 ≤ Ta ≤ +40 |
| Ingress Protection (IP): | 65 |
| Impact Rating (IK): | 06 |
| Power Factor: | 0.95 |
| Operating Voltage: | 100-240 |
| Dimensions W/H/D (mm): | 264/300/183 |
| Box Qty: | 1 |
| Weight (Kg): | 3.04 |

FEATURES

- Range available in 50W Standard, Integral Photocell and Integral microwave versions
- Photocell version automatically switch on at 20 lux and switch off at 60 lux
- Multi-function microwave sensor version has:
 - Adjustable 8m sensitivity range when mounted at 3.5m:
 - Time delay 10s to 12m
 - Adjustable lux level 3 to 2000lx
- High quality COB LED provides:
 - Bright light output - Low power consumption - Long life
- Cool white light colour with high CRI
- Solid state technology
- Die cast Aluminium base with integral heat sink
- Ribbed opaque polycarbonate diffuser with black top panel & internal reflector
- Retained stainless steel fixing screws
- Ingress protection of IP65 and IK06 impact rated
- Supplied with gland and pre-wired through the rear of the fitting with 1.5m 3 or 4 core rubber cable L, E, N (& Ls)

BENEFITS

- Standard fitting provides security lighting with microwave or photocell switching, saving time and difficulty of wiring external sensors
- Three additional fittings can be slaved or parallel wired
- Suitable for security lighting as always on during specified light levels
- Enables additional energy savings to be made when people are not in the area
- Ensures lighting is off when not required
- Area of required operation can be adjusted
- Greater output than 80W or 50W of metal halide so a one for one replacement
- Saves around 40% energy compared to traditional light sources
- Provides excellent visibility and is ideal for safety and security cameras
- No filaments to break or electrode seals to fail which is often a cause of many traditional light source failures – so provides very long life
- Suitable for external PIR, microwave, photocell or time clock control
- Rugged and less susceptible to failure through knocks and vibration
- Strong and durable and provides excellent heat conduction properties to assist in dissipation of heat to keep the LED running cool for longer life
- Excellent aesthetics when light is on or off
- Provides reduced glare
- Ensures light direction is horizontal and downward without unwanted upward light pollution
- Non-rust screws are not lost when fitting is opened to set sensor
- Ideal for outdoor applications
- Less susceptible to damage or vandalism
- Looks neat when mains supply is through wall with no visible cables
- Provides facility to simply wire into a junction box for fast installation
- Switched live loop out on sensor versions

PLEASE NOTE – INFORMATION CONTAINED IN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE