

## DOWNLIGHTS

### COMPACT- LOW & MAINS VOLTAGE PRESSED STEEL FIRE RATED



	MR16	MR16	GU10	GU10
	<b>Straight</b>	<b>Directional</b>	<b>Straight</b>	<b>Directional</b>
White	<b>RFP101-01</b>	<b>RFP108-01</b>	<b>RFP201-01</b>	<b>RFP208-01</b>
Chrome	<b>RFP101-03</b>	<b>RFP108-03</b>	<b>RFP201-03</b>	<b>RFP208-03</b>
B/Chrome	<b>RFP101-13</b>	<b>RFP108-13</b>	<b>RFP201-13</b>	<b>RFP208-13</b>
Lamp Required -35W:	<b>LBK35EA</b>	<b>LBK35EA</b>	<b>LGU1035</b>	<b>LGU1035</b>
-50W:	<b>LBK50EA</b>	<b>LBK50EA</b>	<b>LGU1050</b>	<b>LGU1050</b>
<b>Diameter:</b>	85mm			
<b>Depth:</b>	100mm			
<b>Cut Out:</b>	72mm			
<b>Box Qty:</b>	20			
<b>Weight:</b>	0.21Kg			
<b>Max Power (W):</b>	Max 50W Heat forward with aluminium back			
<b>IP:</b>	20			

Available in a variety of attractive finishes this high quality straight or directional downlight is ideal where the lighting requirement should be fire and acoustic rated. Its shallow design depth of 100mm allows for installation into very small ceiling voids and is suitable for domestic, commercial, retail and many other building types.

THESE FITTINGS ARE NOT SUPPLIED WITH LAMPS. ALUMINIUM BACKED MR16 or GU10 LAMPS ARE RECOMMENDED.

FEATURES	BENEFITS
<ul style="list-style-type: none"> <li>Pressed steel bezel in a choice of colours</li> </ul>	<ul style="list-style-type: none"> <li>Attractive finish for co-ordinating fitting colour to the decor</li> </ul>
<ul style="list-style-type: none"> <li>Pressed steel fire can with Intumescent seals</li> <li>Independent fire testing</li> </ul>	<ul style="list-style-type: none"> <li>Retains the integrity of 30, 60 and 90 minute fire rated ceilings for building regulation part B compliance</li> </ul>
<ul style="list-style-type: none"> <li>Small fire can dimensions</li> </ul>	<ul style="list-style-type: none"> <li>Suitable for installation in shallow ceiling voids</li> <li>Easier installation where air conditioning ducting and pipe work cause issues</li> </ul>
<ul style="list-style-type: none"> <li>Double insulated Teflon lamp holder conductors rated at 250°C</li> </ul>	<ul style="list-style-type: none"> <li>Conductors will not degrade over time providing long service life</li> </ul>
<ul style="list-style-type: none"> <li>Straight and directional versions available in low or mains voltage options</li> </ul>	<ul style="list-style-type: none"> <li>Downlight, wall wash or illuminate displays</li> </ul>
<ul style="list-style-type: none"> <li>Strong single ceiling clips</li> </ul>	<ul style="list-style-type: none"> <li>Ensures the fitting installation looks neat by pulling the bezel tight up to the ceiling</li> </ul>
<ul style="list-style-type: none"> <li>Aluminium backed lamp included</li> </ul>	<ul style="list-style-type: none"> <li>Ensures maximum life of lamp, lamp holder and conductors with heat forward lamp</li> </ul>
<ul style="list-style-type: none"> <li>Spring retained lamp</li> </ul>	<ul style="list-style-type: none"> <li>Fast, easy lamp change</li> </ul>
<ul style="list-style-type: none"> <li>Large termination block with cable clamp</li> </ul>	<ul style="list-style-type: none"> <li>Provides loop in, loop out facility for multiple switching while safely retaining the cables</li> </ul>
<ul style="list-style-type: none"> <li>2 year guarantee</li> </ul>	<ul style="list-style-type: none"> <li>A quality, long life product</li> </ul>

PLEASE NOTE – INFORMATION CONTAINED IN THIS DOCUMENT MAY BE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE