ROBUS°

HILUME LED FLOOD LIGHT, IP65, BLACK, 4000K, C/W 1M FLEX

RHL1040-04 RHL2040-04 RHL10040-04 RHL3040-04 RHL5040-04

PLEASE READ INSTRUCTION BEFORE COMMENCING INSTALLATION AND RETAIN FOR FUTURE REFERENCES.

! Electrical products can cause death or injury, or damage to property. If in any doubt about the installation or use of this product, consult a competent electrician

Product technical information and specification may change over time without prior notification. For the latest technical information please visit our web site www.robus.com.au

-20°C < Ta < +40°C, 220-240V ~ 50/60Hz, Class I, IP65 Luminaire is non-dimmable

Installation

- 1. Ensure mains supply is switched off before commencing work.
- 2. Select suitable location for luminaire.
- 3. Mark wall with appropriate fixing positions. Before drilling, ensure that the hole does not impinge on pipe work, cables or other building services.
- 4. Attach luminaire and fix bracket by tighten screws, then adjust to desired angle. Ensure that it is secure.
- 5. The luminaire is supplied with 1m of rubber cable. Using suitable IP rated enclosure terminate Brown (Live), Blue (Neutral) and Green/Yellow (Earth) to switch supply.
- 6. This product has no user serviceable parts. If any part is damaged, disconnect from mains and discontinue use.

Note: No "fixings screws provided", please use appropriate fixing screws.

The Installation must be carried out by a qualified electrician

Tel: 07 3890 5444

Fax: 07 3890 4777

LED Group Australasia 9/210 Queensport Road North

Murarrie QLD 4172 Australia

LED Group Crowe Hogwarth

72 Trafalgar Square NELSON 7010

Tel: +64 0508 533 335 Email: nz purchases@robus.com

Email: purchases@robus.com

Website: www.robus.com.au

Website: www.robusled.co.nz









