

### SPACE UGR≤19 LED PANEL 30W, IP20



## PRODUCT INFORMATION DOCUMENT

### FEATURES

- UGR≤19 complies with the requirements of EN12464 for reading, writing and computer based tasks in offices and other areas
- The driver primary side is pre-wired with the male half of our SWIFT 4 pole connector with the female part supplied for wiring to the supply infrastructure. Four large terminals allow for a number of conductors for loop in/ out and permanent and switched live supplies
- Luminance <3000cd/m<sup>2</sup> at <65° for ease of screen viewing
- A pre-wired Plug & Play universal DALI, Analogue 1-10v, SwitchDim driver option is Available

### CONSTRUCTION

- White powder coated aluminium frame
- Polystyrene TPb rated diffuser
- Steel back plate



WARRANTY



LIFETIME



LUMENS PER W



IK RATING



IP RATING



OPERATING VOLTAGE



BEAM ANGLE



CCT



SAFETY CLASS

Product Code:	RSP30406060UGR-01	RSP30506060UGR-01
Comparable to:	4 x 18W T8	4 x 18W T8
Total Power (W):	30.8	31
Power Factor:	0.97	0.97
Total Light Output (lm):	3440	3560
Total Emergency Light Output (lm):	NA	NA
Efficacy (lm/ccW):	112	115
Lux at 1m (lux):	1460	1520
Emergency Lux at 1m (lux):	60	60
CCT (K):	4000	5000
CRI:	80	80
IP:	20	20
Operation Temperature (°C):	-20 ≤ Ta ≤ +40	-20 ≤ Ta ≤ +40
Inrush Current:	30.4A/4.4us	30.4A/4.4us
RG Value:	0	0
SDCM:	6	6
P <sub>ST</sub> LM:	NA	NA
SVM:	NA	NA
Energy Class:	D	D
Rated Life to L70B50 (Hrs):	50000	50000
Dimensions ØxH (mm):	595x595x10	595x595x10
Weight (kg):	2.9	2.9
<b>Separate Control Gear Information</b>		
Type of Light Source:	LED	LED
Full Load Efficiency (%):	89	89
P <sub>NET</sub> (W):	NA	NA
Dimensions (mm):	123x45x30	123x45x30

Product is certified to all the relevant standards.

Please contact our technical department for market specific compliances.

PLEASE NOTE: INFORMATION IN THIS DOCUMENT MAY BE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

IRE: TEL: +353 1 709 9000  
UK: TEL: 0800 973 220  
AUS: TEL: +61 7 3890 5444  
NZ: TEL: +64 03 668 5285

WEB: ROBUS.COM  
WEB: ROBUS.COM  
WEB: ROBUS.COM.AU  
WEB: ROBUSLED.CO.NZ

LED GROUP EUROPE · UK · AUSTRALIA · NEW ZEALAND · ASIA · MIDDLE EAST · AFRICA

### SPACE UGR≤19 LED PANEL

30W, IP20

#### Cone Illuminance Diagram





Diagram for RSP30406060UGR-01 in 4000K. Other diagrams available on request

#### Dimension Diagram



#### Sensor Data

Time Off Delay:	NA
Illuminance Switching Range:	NA
Sensitivity Range (%):	NA
Mounting Height (max):	NA
Detection Zone Diameter (max):	NA

#### Polar Intensity Diagram




Diagram for RSP30406060UGR-01 in 4000K. Other diagrams available on request

#### Accessories

HED2040-D	DALI, 1-10V, Switch Dim, 40W Rated Driver
R6060SMKFB-01	Surface Mount Box, 50mm depth
RAMSUS-4W	4 Wire Suspension Kit
RAMSST	Safety Bracket & 2M strap
R3EMPK4-PSU	3 Hour Emergency Pack with LiFePO4 Battery
RAMRC	Plaster Boards Recessed Clips Kit
RPLBRK-01	Panel Adjustable Suspension Bracket