

TOUCAN 18W/36W IP20 LED BATTEN, 4000K, 0.6M/1.2M

RTC184006-01, RTC364012-01

PLEASE READ INSTRUCTION BEFORE COMMENCING INSTALLATION AND RETAIN FOR FUTURE REFERENCES.

! Electrical products can cause death or injury, or damage to property. If in any doubt about the installation or use of this product, consult a competent electrician

Note:

Product technical information and specification may change over time without prior notification. For the latest technical information please visit our web site www.ledgrouprobust.com.au

-20°C < Ta < +40°C, 220-240V~50/60Hz, Class I, IP20

Luminaire is non-dimmable

Suitable for mounting on a normally flammable surface

Installation

1. Ensure mains supply is switched off before commencing work
2. Choose suitable location for mounting the fitting
3. Ensure there is at least 100mm of free space around the fitting location
5. Mark appropriate fixing hole positions on wall, check location of buried cables, pipes and other building services before drilling.
4. Drill mounting holes in wall and then fix the brackets so that it is secure
6. Connect supply power to cables: Brown to L , Blue to N and Yellow or Green to E
7. Attach the fitting to the brackets.



The Installation must be carried out by a qualified electrician

LED Group Australasia
9/210 Queensport Road North
Murarrie
QLD 4172
Australia

Tel: 07 3890 5444
Fax: 07 3890 4777
Email: purchases@ledgrouprobust.com.au
Website: www.ledgrouprobust.com.au

Issue 1 090316

