

QUALITY PRODUCTS BY LED GROUP

OUTDOOR

TWILIGHT IP54 LED SURFACE WALL LIGHT RANGE



No:	1	2	3	4	5	6	7
Comparable to Halogen(W):	10	15	10	30	30	30	15
Total Power (W):	1	2	1	3	3	3	2
Light Output L ₁₀₀ (lm):	30	80	40	180	180	180	80
Efficacy (Im/cctW):	30	40	40	60	60	60	40
Beam Angle (deg):	35	35	42	-	-	-	-
Power Factor:	0.2	0.4	0.2	0.3	0.3	0.3	0.3
Colour Temp L ₁₀₀ (k):	3000						
CRI L ₁₀₀ (Ra):	80						
Rated LED life (hrs):	30,000						
Warranty (yrs):	2						
Ingress Protection (IP):	65						
Impact Rating (IK):	07						
Ambient Operating Temp (°C):	-20≤Ta≤+40						
Dimensions: Width/Dia (mm):	80	230	125	125	230	150	150
Height (mm):	200	80	125	125	80	-	-
Protrusion (mm):	27	27	27	27	27	27	27
Min Order Qty/Carton Qty:	1/24	1/24	1/40	1/40	1/24	1/40	1/40
Weight (Kg):	0.17	0.22	0.18	0.2	0.23	0.21	0.19

This great range of outdoor fittings, manufactured from Polycarbonate, look superb whilst providing a gentle guide light function. The range has a wide choice of aesthetics and designs all of which are very energy efficient and do not suffer from lamp failure associated with traditional light source technology.

Surface mounted, these fittings are typically installed in domestic applications in walkway locations around the property, but can equally be used to excellent effect in sheltered housing schemes, hotel and restaurant or pub terrace and patio applications without worry of burning if touched by children.

FEATU	JRES	BENEFITS		
	oice of circular, square, and rectangular vertical or rizontal modern designs in an attractive dark grey ish	Great aesthetics with an individual look Colour matches or contrasts with many outside decors Choice of modern stylish designs		
pol	se and diffusers manufactured from UV stabilised lycarbonate p-on cover with no exposed screws	 Strong and durable High quality finish and will not rust which will look good for many years Class 2 device, no earth required so provides more internal cable space Fast and simple removal of cover for mounting of base and cable termination Great for coastal applications as will not rust and discolour walls 		
 Op- 	lycarbonate diffusers valised for those with horizontal light beams and plain or downward light beams	 Maximises light output without glare Provides a uniform light spread 		
• Im	pact rating of IK07	Not easily damaged by knocks and bangs to provide long life		
• Ing	gress protection to IP65	 Ideal for installation outdoors Ensures water or dust cannot enter the fitting so provides long life 		
• Util	ilises high quality SMD LED's to provide: Excellent guide lighting Low power consumption High efficacy Long LED life	 Compared to traditional halogen or incandescent light sources: Comparable light output Provides energy savings of over 80% so have very low running costs Last up to 20 times longer so no annoying dark areas or lamp changes required over life 		
• Hig	gh quality, high CRI warm white light	Provides a subtle warm complimentary lighting ambience		
• Int	egral driver	No separate enclosure required for power supply		
• No	Infra-red or Ultra-violet in the light beam	 Is cool to touch so will not burn if touched Does not attract most flying insects 		

PLEASE NOTE - INFORMATION CONTAINED IN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

